

Product and Company Identification

Product Name: **DF Series**
 Manufacturer's Name: **Prospec Specialties Inc.**
 100-1075 North Service Rd.W,
 Oakville On L6M2G2, Canada
 Emergency #: (888) 749-8456


Table 1: System Details

Application	Code	JO	SH	SW	± Movement (%)			Load (Ton)
		Millimeter			Horizontal	Vertical	Shear	
Straight (S)	DFS 025	25	38	117	50	25	Excellent	3
	DFS 050	50	38	140	50	25	Excellent	3
	DFS 075	75	38	197	50	25	Excellent	3
	DFS 100	100	38	222	50	25	Excellent	3
	DFS 150	150	38	342	50	25	Excellent	3
	DFS 200	200	38	457	50	25	Excellent	3
Corner (C)	DFC 025	25	38	70	25	25	Excellent	3
	DFC 050	50	38	95	25	25	Excellent	3
	DFC 075	75	38	137	25	25	Excellent	3
	DFC 100	100	38	162	25	25	Excellent	3
	DFC 150	150	38	248	25	25	Excellent	3
	DFC 200	200	38	329	25	25	Excellent	3

JO = Joint Opening **SH** = System Height **SW** = Sight Width

Key to System Features (Straight Application)

- Continuous Aluminum Center Plate, Grade 6063-T6
- Continuous Aluminum Recessed frame, Grade 6063-T6
- Steel Centering Bar
- Compression Spring Assembly
- Hex Head Concrete Anchor (by others)
- Back fill (by others)
- Concrete Slab (by others)



Key to System Features (Corner Application)

1. Continuous Aluminum Half Plate,
Grade 6063-T6
2. Continuous Aluminum Recessed Frame,
Grade 6063-T6
3. Continuous Aluminum Flush Wall
Frame,
Grade 6063-T6
4. Hex Head Concrete Anchor (by others)
5. Countersunk Head Screw (by others)
6. Back fill (by others)
7. Concrete Slab (by others)
8. Concrete Wall (by others)

