

Product Description

General	Aluminum cassette profile held firmly by PVC coated steel cables and EPDM spacer for fall-thru action
Aesthetic aspect	Rubber wipers, Black EPDM spacers with open construction

Technical Specifications

Physical Properties

Thickness	24mm
Wiper surface	27mm
Cassette profile material	Mill Finished Aluminum, grade 6063-T6
Wiper strip material	E.P.D.M. Rubber
Connector material	PVC coated Stainless Steel cables
Spacer Material	Black E.P.D.M.
Wiper Spacing	5mm
Format	Roll-able
Design	Open
Mat module size	Module dimensions to be decided by factory production
Weight/Square Meter	41.88 lbs (19 kgs)
Maximum rolling load/wheel, Recessed installation	1000 lbs.
Frame options	Welcome mat-well frame of silver anodized aluminum, grade 6063-T6

Component Color Options

Wiper strip	Grey
-------------	------

Product Properties

Performance	Standard	Result
Critical Radiant Flux	ASTM E648	Class 1
Coefficient of Friction	ASTM D2047	Meets or exceeds ADA guidelines
Rolling Load	ASTM F2753	Able to sustain 1000 passes without damage
Corrosion (Salt Spray)	ASTM B117	Able to sustain 100 hours of salt fog without any notable changes

LEED

MR Credit 4	LEED-NC v.3	For 1-2 points: value of all materials = min. average 10% recycled content	40% pre-consumer and 40% post-consumer recycled
IEQ Credit 5	LEED-NC v.3	For 1 point: permanently installed entrance mats at least 10' long	Mat designed for permanent installation