


Product and Company Identification

Product Name: **WC-15** (Proteger Wall Covering)

Manufacturer's Name: **Prospec Specialties Inc.**

100-1075 North Service Rd. W, Oakville
On L6M2G2, Canada

Emergency #: (888) 749-8456




SEMI-RIGID SHEET

System Details

- Thickness: 1.5mm
- Size: 1200mm x 2400mm
- Material: **FSS[®]Polyvinyl**
- Adhesive mount
- High impact resistance
- Enhances appearance
- Durable
- Reduces maintenance costs
- Application: Hospitals, Clinics, Cleanrooms & Kitchens

Physical Properties

- Weight: 1.5 kg/m²
- Density: 1.05 g/cm³
- Max Service Temperature: 90°C
- Hardness: 96 MPA
- Notched impact resistance: 101 J/M
- Flexural strength: 50 MPA
- Tensile strength: 68 MPA
- E-modulus of electricity: 87°C
- Heat distortion: 2.5 GPA



SECTION DETAIL

Quality Assurance & Tests:

- Passed Anti-Fungal Anti-Microbial Test as per ASTM G 21
- Passed Chemical Resistance Test as per ASTM D2240
- Passed Chemical Resistance Test as per ASTM D543
- Passed Flame Resistance Test as per UL 94
- Passed Impact Resistance Test as per ASTM E 2486
- Passed Smoke and Spread of Flame Test as per ASTM E 84
- Single source manufacturer.
- Installation / Method Statements available for successful installation
- Color consistency in accordance with SAE J-1545-(Delta E) with a color difference no greater than 1.0 units using CIE Lab, CIE CMC, CIE LCh, Hunter Lab or similar color space scale systems.